



Technical requirements:

1. There is no scratch on the surface of the product, no sharp edge, sharp Angle, burr, etc. ;
2. The products must be assembled in strict accordance with the design process requirements and product-related standards;
3. Unmarked tolerance is m class (medium class) according to tolerance class (GB/T 1804-2000).

8	GB/T 70.1-2008	Hexagon Socket Cylindrical Head Screw	M8×16	4	SUS304	0.012	0.048	
7	V02-0020.A100	CMN Fixture Block	SL-V02-0020	2	AL6005-T5	0.014	0.028	
6	GB/T 70.1-2008	Hexagon Socket Cylindrical Head Screw	M8×25	2	SUS304	0.017	0.034	
5	L93-0018.B200	Spring	HOP-L93-0018	2	SUS304	0.001	0.002	
4	GB 861.1-1987	M8 Internal Tooth Washer	d8	8	SUS304	0.002	0.016	
3	GB/T 70.1-2008	Hexagon Socket Cylindrical Head Screw	M8×45	2	SUS304	0.023	0.046	
2	V03-0045.A100	30-40 CM Clamp	SL-V03-0045	2	AL6005-T5	0.037	0.074	
1	W03-0045.A100	10° Rear Foot Support	SL-W03-0045	2	AL6005-T5	0.284	0.568	
No.	Part No.	Name	Spec./Dwg No.	Qty	Material	Weight(kg)		Remark
						Piece Weight	Gross Weight	

SUN-LOCK

Version	A/0	View		Design		Material		Part Name	East And West Support 10° Rear Foot Set
Scale	A4	Review		Weight	0.82kg	Part No.	SLCTL2-10EW	Dwg No.	SLCTL2-10EW
Mark	Qty	Updated Content	Sign	Date	Approve				